BELL SYSTEM PRACTICES
Station Installation and Maintenance

SECTION C14.008 Issue 1, Feb., 1956 AT&TCo Standard

SPEAKERPHONES



Fig. 1—Speakerphone Components—Microphone Separate (Control Unit Not Shown)



Fig. 2—Speakerphone Components—Microphone in Base of Set (Control Unit Not Shown)

Popular Names

Speakerphone Distant talking set Hands free set

Standard Nomenclature

Speakerphone System 1A 595-type Telephone Set

Features

- Provides 2-way conversation with or without use of handset.
- Speakerphone facility may be provided by one of two arrangements.
 - (1) Either a key or keyless telephone set is used with a separate loudspeaker and a separate transmitter (microphone) unit on which are mounted the control buttons (see Fig. 1).
 - (2) A 592-type telephone set, on which are mounted a transmitter (microphone) and the control buttons, is used with a separate loudspeaker (see Fig. 2).

A control unit containing the amplifier and switching equipment is required in either arrangement.

- The ON control button may be depressed to answer a call or to ready the telephone set for dialing. A pilot light illuminates this button when the speakerphone facility is in use.
- The OFF control button disconnects the speakerphone facility and restores the telephone set to normal use.
- The VOL control knob is provided to adjust volume of loudspeaker unit.
- The 592-type telephone set is available in the eight full and eight two-tone colors or black. Handset cord may be straight or retractile—color or black as appropriate. Mounting cord is straight, standard length only—color or black as appropriate.
- The 656A transmitter assembly is equipped with a 5-foot, 6-inch cord. Housing and cord are available in color or black to match associated telephone set.
- The 758A loudspeaker is equipped with a 5-foot, 6-inch cord. Housing and cord are available in color or black to match associated telephone set.

Charges

Recurring charges (monthly rate)	
Business:	
Residence:	
Nonrecurring charges	
Service connection:	
Change charge:	