

STANDARD RINGING CODES

For 10-Party Frequency Ringing

Ringing Digit	Side of Line	Ringing Code	Frequency of ringing voltage (CPS)				
			33-1/3, 30	50, 42	66-2/3, 54	16-2/3, 66	25 Harmonic, 20 Synchronomic, 20 Decimonic
1	Neg.	1 long	X				
2	Neg.	1 long		X			
3	Neg.	1 long			X		
4	Neg.	1 long				X	
5	Neg.	1 long					X
6	Pos.	2 shorts	X				
7	Pos.	2 shorts		X			
8	Pos.	2 shorts			X		
9	Pos.	2 shorts				X	
0	Pos.	2 shorts					X

For 10-Party Bridged Code

Ringing Digit	Side of Line	Ringing Code
1	Neg.	1 long
2	Neg.	2 short
3	Neg.	4 short
4	Neg.	2 long
5	Neg.	2 long 1 short
6	Pos.	2 short 1 long
7	Pos.	2 short 1 long 1 short
8	Pos.	1 long 1 short
9	Pos.	1 long 2 short
0	Pos.	1 long 3 short

For 8-Party Superimposed

Ringing Digit	Side of Line	Ringing Code	Ring Polarity
1	Neg.	1 long	+
2	Neg.	1 long	-
3	Neg.	2 short	+
4	Neg.	2 short	-
5	Pos.	1 long	+
6	Pos.	1 long	-
7	Pos.	2 short	+
8	Pos.	2 short	-