



- NOTES
1. "X" CONTACTS TO BREAK LAST.
  2. IF BELL TAPPING IS ENCOUNTERED WHEN DIALING FROM ANOTHER TELEPHONE ON A BRIDGED LINE, REVERSE RINGER CONNECTIONS AT TERMINALS 9 and 16 OF TRANSMISSION BOARD.
  3. WIRING FOR DESK INSTRUMENT (WITH LINE CORD AND CONNECTING BLOCK) SHOWN FOR METALLIC BRIDGED RINGING. WIRING OF WALL INSTRUMENT (DIVIDED) RINGING.
  4. REQUIRED LEAD FOR FIELD CONVERSION TO TIP PARTY IDENTITY.
  5. WHEN MESSAGE WAITING LAMP IS USED CONNECT ACROSS TERMINALS 8 AND 10 OF TRANSMISSION BOARD.
  6. LINE CORD AND CONNECTING BLOCK PROVIDED WITH DESK INSTRUMENT ONLY.
  7. "Y" CONTACTS ON COMMON SWITCH BREAK FIRST.
  8. EXTENSION TELEPHONES WITHOUT RINGERS USED WITH TIP PARTY AUTOMATIC NUMBER IDENTIFICATION WILL REQUIRE THE USE OF A SEPARATE INDICATOR FOR IDENTIFICATION.

Type 182A Telephone Set (NC-820) with Old-style Touch Calling Unit, Schematic and Wiring Diagram.