



- NOTES:**
- FUSE:- FIGS. 1 & 3 1.5A PER 2 CCTS.
FIG. 4 1.5A PER 10 CCTS.
FIG. 5 1.5A PER CIRCUIT.
 - Ø FOR WIRING SEE ASSOC'D COMMON SERVICES DIAGRAM.
 - UNLESS OTHERWISE SPECIFIED ALL WIRING TO BE 0.5 mm.
 - SHELF JACK POINT U9 & U11, U13 & U15 TO MAKE CONTACT WHEN RELAY SET 15' REMOVED.
 - FAULTS SERVICES NOT EXTENDED TO MANUAL BOARD TO BE BUSIED OUT BY INSERTION OF STRAP BETWEEN U9 & U29 FOR 1ST. CCT. OR U31 & U13 FOR 2ND. CCT.
 - WHEN RELAY FOR INCREASED APPEARANCES IS REQUIRED E.G. EXCESS OF 5 POSITIONS ADD WIRING THUS -1-1-1- AND DELETE WIRING THUS -2-2-2- OTHERWISE WIRING THUS -2-2-2- IS PROVIDED.
 - STRAP U10 & U18 &/OR U10-20 INSERTED FOR LINES WHICH ARE NOT NIGHT BUSIED.
 - WHEN I.D.F. IS NOT REQUIRED CABLE DIRECTLY FROM RELAY SET TO DESK AND/OR LAMP RELAY OR TO TURRET AS SPECIFIED.

SUPERSEDED BY GBW 13880 50V. H

FAULTS SERVICE LINES TERMINATING ON TEST OR FAULTS SERVICE DESK OR EQPT. WITH OR WITHOUT NIGHT SWITCHING TO AUTO-MANUAL BOARD S.C.S.

| ISS DATE | DEL | DC | ORDER | CKD | APD | CHANGE |
|------------------------------------|------|----|-------|-----|-----|---------------------------------|
| 27.5.50 | E.U. | | 77165 | | | RETRACTED & METRICATED. |
| 11.12.51 | | | 50994 | | | D.M. SUPPRESSION NOTE ADD. |
| 14.10.52 | | | 55255 | | | J.R. FAULT SERV. WKS COMPLAINTS |
| | | | | | | FIG. 2 LAMP LEADS MOD. |
| | | | | | | TITLES OF FIGS 1, 3 & 5 MOD. |
| | | | | | | FIGS. 1, 2 & 3 MOD. |
| | | | | | | RETRACTED |
| DRN T-EQPT CKD ORIGIN T-EQPT | | | | | | |
| TCDD E.U. APPD STANDARD ATW22001 | | | | | | |
| NZPO ENGINEER-IN-CHIEF, WELLINGTON | | | | | | |
| A1 GBW 10560 | | | | | | |

PROOF