



- 11 WHEN USED FOR UNI-DIRECTIONAL LINE (TRAFFIC TO EXCHANGE) DELETE JUMPERS SHOWN - - - - - AND PROVIDE THOSE SHOWN - - - - -
1. FUSE 1 AMP PER 25 CCTS.
2. Ø FOR WIRING SEE ASSOCIATED COMMON SERVICES DIAGRAM.
3. ALL WIRING TO BE 25 SWG UNLESS OTHERWISE SPECIFIED.
4. D2, D3 & D4 OUTLETS 1-23 ARE MULTIPLIED OVER ALL UNISELECTORS IN EACH GROUP OF 25. ON OUTLET 24, D3 ONLY IS MULTIPLIED.
5. AT SOME EXCHANGES WIPER DI MAY BE BRIDGING.
6. WHEN CLIP-ON TUBULAR TYPE CONDENSERS ARE FITTED PROVIDE FIG. 1F AND CONNECTIONS SHOWN -X-X- IN LIEU OF FIG. 1C & CONNS. SHOWN -O-O- WHEN B.P.O. TYPE 7731 CAPACITORS ARE FITTED, PROVIDE FIG. 1J AND CONNECTIONS SHOWN -||-||-

- NOTES
- 7 THESE LEADS MAY, WHEN SPECIFIED, BE CABLED OR WIRED FROM I/C SHELF STRIP CONN. TO RURAL PARTY LINE REPEATER (RSR OR U/S RACK) IN WHICH CASE FIG. 1E IS NOT CONNECTED. ALTERNATIVELY THEY MAY BE CABLED TO 2-PARTY DISCRIMINATION CIRCUIT (MAR.) FOR ACTUAL CONNECTIONS SEE RELEVANT DIAGRAMS.
- 8 AT EXCHANGES WITH FLOOR TYPE MDF USE FIGS 1A & 1D. AT EXCHANGES WITH RACK TYPE MDF OR WITH FLOOR-TYPE MDF FITTED WITH TEST JACKS N° 32A USE FIGS 1G & 1H.
9. FOR PBX BUSYING, TRANSFER LINK FROM BI-B2 TO BI-P
10. THIS CIRCUIT MAY BE USED ON EXCHANGE EXTENSIONS IN ORDER TO COMPLETE THE EQUIPMENT OF EXISTING RACKS. IN SUCH CASES BATTERY WIRING MAY BE V

NOTES 12. WHEN LINE CCT. IS ASSOCIATED WITH A PBX EXCH. LINE CCT. GBW15220 OR EQUIV. THE EARTH IS TO BE REMOVED OFF K4 (FIG. 1B).

SUPERSEDED BY GBW14790 NOTE 1C

NEC LLE & IZA-ANI CONNECTIONS SHOWN	B	13-3-81	JR
REF. NZM.PT. (129098)	A	19-8-77	JR
AMENDMENT PARTICULARS	ISSUE	DATE	APP'D
NZPO	DRAWN	CHECKED	WIRED
	DRW		50/10/50
			ENGINEERS

SLOW RELEASE     SLOW OPERATE

**SUBSCRIBERS LINE CIRCUIT.**

50V E

**GBW 10752 MOD. A**