



- NOTES**
1. FUSING:- 1.5A PER CCT.
  2. DIAL TONE IS ONLY PROVIDED ON SUBSCRIBERS FIRST SELECTORS IN NON DIRECTOR AREAS.
  3. P.G. ALARM BATT. PROVIDED ONLY ON I/C AND LOCAL 1ST SELRS. P.G. OVERLOAD ALARM BATT. PROVIDED ONLY ON LOCAL 1ST SELRS.
  4. Ø FOR WIRING: SEE GBW 10670 OR EQUIV.
  5. WHEN USED AS SUBSCRIBERS FIRST SELECTOR IN UNISELECTOR EXCHANGES STRAP U8 TO U9.
  6. WHEN FULL AVAILABILITY TO NEXT RANK SELECTOR IS SPECIFIED OUTLETS ARE CABLED DIRECT FROM BANK MULT STRIP CONN TO NEXT RANK SELECTOR AND NOT VIA T.D.F.
  7. 'P' LEAD NOT REQUIRED WHEN + AND - LEADS ARE CABLED TO M.D.F.

BATT. (W):- U12-HB2-YB2-YC2-Ae-HAe-Ve-Re-YE2  
 EARTH (R):- U11-Cd-C4-Ab-HA9  
 B1-B5-S6-QA5-T7-T9

				<b>200 OUTLET GROUP SELECTOR 2000 TYPE</b>			
RETRACED. NO AMENDS.	157670	5B	28-7-78	RED.			
NOTE 3 AMD. TO SAME AS NOTE 3 GBW 10760	176041	5A	31-3-78	RED.			
RETRACED. NO AMENDS.	SJR	72415	5	13-3-64	D.B.H.		
AMENDMENT PARTICULARS				ORDER	ISS.	DATE	APPD
				REF: GE	S8600	SIZE A2	50V H
NZPO		DRAWN	CHECKED	WIRING	CIRCUIT	<b>GBW 10761</b>	
		C.T.M.	K.C.	KC	H.B.		