



- NOTES:
- 1 FUSING: - 1.5A PER CCT.
  - 2 DIAL TONE IS ONLY PROVIDED ON SUBSCRIBERS FIRST SELECTORS.
  - 3 PG. ALARM BATT. PROVIDED ONLY ON 1/3 AND LOCAL 1ST SELRS.  
PG. OVERLOAD ALARM BATT. PROVIDED ONLY ON LOCAL 1ST SELRS.
  - 4 Ø FOR WIRING SEE GBW 10670 OR EQUIV.
  - 5 WHEN USED AS SUBSCRIBERS FIRST SELECTOR IN UNISELECTOR EXCHANGES OR WHEN PRECEDED BY GBW 12680 STRAP U8 TO U9.
  - 6 WHEN FULL AVAILABILITY TO NEXT RANK SELECTOR IS SPECIFIED OUTLETS ARE CABLED DIRECT FROM BANK MULT. STRIP CONN TO NEXT RANK SELR. AND NOT VIA I.D.F. SEE GBW 14850.
  - 7 P LEAD NOT REQUIRED WHEN + AND - LEADS ARE CABLED TO M.D.F.
  - 8 ALL WIRING TO BE 0.5mm UNLESS OTHERWISE SPECIFIED.
  - 9 SHELF JACK POINTS U9 & U11 TO MAKE CONTACT WHEN SELR. IS REMOVED.

ETH R 0.7mm (1A) U11  
 BAR  
 BATT FUSE BK 0.7mm (1B) U12

ETH R-U11-CD4-Ab-HA9-B1-B5-S6-R5a-TJ7-TJ9  
 BATT. W:- U12-HBe-R3b-Ae-HAe-VMe-RMe

|   |  |   |  |        |          |        |                      |
|---|--|---|--|--------|----------|--------|----------------------|
| S   |  | N |  | NR     |          | TJ     |                      |
| 2   |  | 4 |  | 5      |          | 14     |                      |
| RETRACED & METRICATED (157669)                  |  |   |  | 2B     | 16-11-78 | R.E.D. |                      |
| NOTE 3 AMD TO READ AS NOTE 3 GBW 10760 (176043) |  |   |  | 2A     | 22-3-78  | R.E.D. |                      |
| 1/3 CONN. FROM SELRS REVISED. (69171)           |  |   |  | 2      | 20-9-63  | D.B.H. |                      |
| AMENDMENT PARTICULARS                           |  |   |  | ISSUE  | DATE     | APPD   | REF. GEC. DRG. S8600 |
|   |  |   |  | SIZE   | A2       | 50V    | H                    |
| NZPO  |  |   |  | DRAWN  | CHECKED  | WIRING | CIRCUIT              |
|   |  |   |  | P.E.R. | NJL      | NJL    | H B                  |
|   |  |   |  | GBW    |          |        |                      |

**200 OUTLET GROUP SELECTOR**  
 100 TYPE

10762