GBW 10792

T.D.F. O/G

NOTE 5

FROM SELECTOR LEVELS

TRAFFIC Ø RECORDER

NOTE. 9.

TERMINALS ON FINAL SELR RACK

TO SUBS LINE CIRCUIT. NOTE-2.

BATT. V 0·7 m.m FUSE (7B) — U12

EARTH R. 0·7 m.m. ETH BAR (7A) — U11

NOTES CONT'D

10 CONNECTION OF LINES 10 & 11 ON P2 BANK
UPPER HUNDRED LINE 11 STRAP MISC. TAG 92 } TO BATT. TAGS (VA) OR EARTH TAGS (E) ON
LOWER HUNDRED LINE 11 STRAP MISC. TAG 32 } MULTI STRIPS CONN. AS REQUIRED.

UPPER HUNDRED LINE 10 STRAP MISC. TAG 93 } TO ETH TAGS (E) ON MULT.
LOWER HUNDRED LINE 10 STRAP MISC. TAG 33 } STRIPS CONN. AS REQUIRED.

N	NR	TJ
3	4	14

4 Ø FOR WIRING SEE G.B.W. 10080 OR EQUIV.

NOTES :-

1. FUSE :- 1·5A PER CIRCUIT. POS. BATT – 0·5A PER 10 CIRCUITS.
2. CONTACTS 11 OF LEVEL 1 (REVERSE NUMBERED N.Z. DIAL) OR LEVEL 9 (STANDARD B.P.O. DIAL) TO BE MULTIPLED AND WIRED TO MISC. STRIP CONN
3. CONNS. OF P2 BANKS :-

P.B.X. GROUP: FIRST LINE, INTER LINES, LAST LINE, ORD. LINES — 200, 200, 200

5. WHEN FULL AVAILABILITY FROM GROUP SELECTORS IS SPECIFIED, INCOMING LEADS ARE CABLED DIRECT FROM BANK MULT. STRIP CONN. AND NOT VIA T.D.F. IN SUCH CASES THE FOLLOWING STRAPS MUST BE APPLIED ON SITE.
   a) IN ALL CASES STRAP U11 TO U7.
   b) WHEN NO SELECTOR IS EQUIPPED STRAP U9 TO U7 EXCEPT WHERE GBW 14850 NOTE 2,9 APPLIES.
6. ALL WIRING TO BE 0·5 m.m, UNLESS OTHERWISE SPECIFIED.
7. WHEN A CENTRALISED I.D.F. IS SPECIFIED THE –,+ & P TERMINALS ON THE BANK MULT STRIP CONN ARE CABLED TO T.D.F. MULT.
8. ON EARLY EQUIPMENT, NEG. & POS. BATT. WIRING WAS BK OR W AND R-B RESPECTIVELY.
9. WHEN LOCAL METERING IS NOT REQUIRED INSERT STRAP AS SHOWN THUS —|—

TAGS ON SHELF MISC. STRIP CONN..

PAIRS IN MULT ONLY SINGLE TAILS

NOTE 3

AMENDMENT PARTICULARS	ISSUE	DATE	APPD
RELAY E COIL TAG CORRECTED TO 6 (113112)	8A	18.6.86	G.G.G.
REPLACEMENT TCG (NCORD (99918)	8	27.8.73	B.S-H
	1	7.10.53	C.R.

NZPO — AT&E CO. LTD. LIVERPOOL — W.L.B. — APPD A.P.O. 6.10.53 — DRAWN G.C. — CHECKED A.P.O. 27/8 — WIRING CIRCUIT

REF. : G.E.C. DRG. S 6503 — SIZE M — SIZE 50" H

200 LINE FINAL SELECTOR
2-10 P.B.X.
POSITIVE BATTERY METERING
2000 TYPE.

SLOW RELEASE — SLOW OPERATE