



UD 237

FIG. 1 (PART OF)

FIG. 2

FIG. 3 (FOR ETH. RUN SEE FIG. 2)

FIG. 1 PROOF

- NOTES:
- CONTACTS OF A1 ARCS STRAPPED TO 'EQ' TAGS IF EQUIPPED & TO 'UN' TAGS IF UNEQUIPPED. TERMINAL ALLOCATIONS ARE AS FOLLOWS:
 FOR ACC. SW. 1 TX3/1-20 RESPECTIVELY TO TX2/1-20 IF EQUIPPED & TO TX4/1-20 IF UNEQUIPPED.
 2 TX5/1-20 TX6/1-20 TX4/1-20
 3 TX7/1-20 TX8/1-20 TX4/1-20
 4 TX9/1-20 TX10/1-20 TX4/1-20
 5 TX11-10 TX11-10 TX11-10
 - CONTACTS OF SD1 ARC STRAPPED TO 'ED' TAGS IF EQUIPPED & TO 'UN' TAGS IF UNEQUIPPED.
 - ALL WIRING TO BE 0.7mm. UNLESS OTHERWISE SPECIFIED, BARK WIRING TO BE 0.5mm.
 - Ø FOR WIRING SEE ASSOCIATED COMMON SERVICES DIAGRAM.
 - METERING, NON METERING, ORDINARY & FORWARD HOLDING RELAY SETS MUST NOT BE MIXED ON SHELVES SERVED BY ONE ACCESS SWITCH.
 - TERMINALS ASSOCIATED WITH ACCESS SWITCHES SERVING FORWARD HOLDING METERING A/A RELAY SETS TO BE STRAPPED TO TR3/10 AS SHOWN THUS:
 TERMINALS ASSOCIATED WITH ACCESS SWITCHES SERVING FORWARD HOLDING NON METERING A/A RELAY SETS TO BE STRAPPED TO TR3/11 AS SHOWN THUS:
 TERMINALS ASSOCIATED WITH ACCESS SWITCHES SERVING ORD. NON METERING A/A RELAY SETS TO BE STRAPPED TO TR3/10 AS SHOWN THUS:
 NO STRAPPING IS REQUIRED FOR ORDINARY METERING A/A RELAY SETS.
 - ON ARCS 2-B OF ACCESS SWITCH 5 OUTLETS 1-10 ONLY ARE WIRED.
 - WHEN THE ASSOCIATED A/A RELAY SET IS TO GO IN (1250 OR 68W 12550) THE P IN LEAD (U9) IS WIRED IN R-B AND THE HA OR RT LEAD (U8) IN R-O.

NOT TO BE USED FOR NEW WORK

ROUTINER ACCESS SELR. U/S
WITH SECY. DISTR. FOR A/A
ORD. & FWD. HOLDING R/S
2000 TYPE

22-30-55	17160	RETRACED & METRICATED
15-6-68	79503	DRAWING NOT TO BE USED FOR NEW WORK ADDED
15-4-57	68573	WHEN NOTE B ADDED
15-1-53	153-345	ENR
ISS DATE	DEL DC ORDER CKD APD	CHANGE
DRN: 5-5 SECT. CKD	ORIGIN: 5-5 SECT.	
TCD: N.S.	APPD	STANDARD: ATW 22001
NZ PD ENL	IN-CHIEF, WELLINGTON	
SH1 1 OF 1	GBW 11551	
SIZE A1		

