



- NOTES:**
- FUSE - 1.5 A PER CIRCUIT.
  - Ø FOR WIRING SEE GBW 10660 OR EQUIVALENT.
  - WHEN FULL AVAILABILITY FROM GROUP SELRS IS SPECIFIED INCOMING LEADS ARE CABLED DIRECT FROM BANK MULT STRIP AND NOT VIA IDF IN SUCH CASES WHEN THE SELECTOR IS NOT EQUIPPED STRAP U POINTS 9 & 11 EXTERNALLY EXCEPT WHERE GBW 14850 NOTE 2-9 APPLIES.
  - WHEN A CENTRALISED IDF IS SPECIFIED THE - , + & P TERMINALS ON THE BANK MULT STRIP CONN ARE CABLED TO IDF MULT.
  - WHERE ALTERNATIVE MECH SPRING SET NOS ARE SHOWN (A) 1/8 & 2/9 ETC. THE N# BEFORE & AFTER THE OBLIQUE STROKE APPLY TO TYPE 2 & TYPE 1, SPRINGSETS RESPECTIVELY. N# WITHOUT AN OBLIQUE STROKE APPLY TO BOTH TYPE OF SPRINGSETS.
  - U9 & U11 TO MAKE CONTACT WHEN SELECTOR IS REMOVED.
  - ALL WIRING TO BE 0.5mm. UNLESS OTHERWISE SPECIFIED. BANK WIRING AND SELECTOR WIRING TO BE 0.5mm.
  - ON SOME EQUIPMENTS COMMONS BETWEEN UNISELECTOR BANKS ARE IN 0.5mm. ORANGE AND NOT IN THE COLOURS SHOWN IN THESE CASES THE ROUTING SHOWN THUS SHOULD BE USED

- N.Z. NOTES:**
- ON EQUIPMENT PRIOR TO 155, G CONTACT MG3 WAS WIRED IN SERIES WITH U30 AND H7 AND SHORT CIRCUITED.
  - ON SOME EARLY EQUIPMENT COLOUR OF BATT. WIRING WAS BK OR W & POSITIVE BATT. WAS R-B.
  - WHEN LOCAL METERING IS NOT REQUIRED INSERT STRAP SHOWN THUS -|-

**NOTE 8:**

TO PULSE GENERATOR RELAY SET GBW 11930 OR EQUIVALENT

ETH. ETH. BAR 0.7mm. R (YQD1, RL11, U11)

BATT. V. FUSE 0.7mm. V (RL4, U12)

ETH. R. U11-H27-FR6-PL1-DB24-C25-C4-C6-DR21-DR25-AC3-D2-TRA'E-Ab-B25-B21-B6-BA1-DA6-DA3-J22-(MRA2) FF21-F2-MRA1-YQ1-TZ

BATT. V. U12-MGe-He-FRb-FRe-RLe-DRe-ACe-De-YC2 Ae-BAb-BAe-Je-Fe-YD2-YE2-YG2-Ve-Re

POS BATT. U20, YA2

**NOTE 9:**

21 RL 5/1 - 22 RL 3/1 TO 30 RL 3/1 R-BK GBW 11930

21 RL 3/12 - 22 RL 3/12 TO 30 RL 3/12

1 RL 3/1 - 2 RL 3/1 TO 20 RL 3/1

1 RL 3/12 - 2 RL 3/12 TO 20 RL 3/12

**NOTE 11:**

TO OVERCOME THE PREMATURE OPERATION OF RELAY F DUE TO EXCESSIVE LINE CAPACITY RELAY CONTACTS F2 ARE TO BE CONNECTED. ED AS SHOWN -a-a-

PROOF

100 LINE RURAL FINAL SELR ORDINARY POSITIVE BATTERY 2000 TYPE	
RETRACED FROM 155 BA OF 23-5-72 (17047)	BB 29-2-60
NOTE 11 ADD N.Z. NOTE A AND N.Z. NOTE B DEL (30433)	BA 23-5-72 B.S.H
AMENDMENT PARTICULARS	155 DATE APD
SIZE A1 50V C	
GBW 11790	
N.Z.P.O.	DRAWN EU CHKD WIRING CIRCUIT

0  
5 Centimetres  
10  
15  
20  
25  
30  
35  
40

N	NR	T
3	4	14

R-O  
CODE START  
GBW 11930  
OR EQUIV.

R-B-G  
R-B-N  
CODE CODE  
HOLD, OPERATE  
GBW 11930  
OR EQUIV.