


NOTES:

1. FUSING 1.5A PER 2 CIRCUITS.
2. U POINTS 9,11 AND 17,19 TO MAKE WHEN RELAY SET IS REMOVED
3. Ø FOR WIRING SEE GBW 10640 OR EQUIVALENT.
4. WHEN FULL AVAILABILITY FROM SELECTOR LEVELS IS SPECIFIED INCOMING LEADS ARE CABLED DIRECT FROM BANK MULT STRIP CONNECTION, AND NOT VIA T.D.F.

ETH. ETH. BAR 0.9mmR (3A) U11-U17  
 BATT. FUSE 0.9mmBK (3B) U12  
 ETH(R) U11-Da-B22-B4-B22-B4-Da-Lb-L1-DD1-DD1-Lb-L1-T1-T1  
 BATT. (W) U12-De-Be-Be-De-Lc-DDe-DDe-Le



		SLOW RELEASE		SLOW OPERATE	
<b>TOLL PRICES RELAY SET (NON-METERING) 2000 TYPE EQUIPMENT.</b>					
RETRACED & METRICATED		(154592)	1A	10-5-78	R.E.D.
		(11967)	1	26-8-52	
AMENDMENT PARTICULARS			ISSUE DATE	APPD.	SIZE S 50V S
NZPO		DRAWN	CHECKED	WIRING	CIRCUIT
<b>GBW 12040</b>					