



NOTES:-

1. WHEN EXTENSION BELL REQUIRED, REPLACE 3-CONDUCTOR CORD WITH 4-CONDUCTOR CORD AS SHOWN THUS AND REMOVE STRAP SHOWN THUS
2. CONNECTIONS ARE SHOWN FOR METERED STATIONS WITH RINGING ON B-WIRE FOR ALL OTHER STATIONS, TRANSFER BLUE DIAL CORD CONDUCTOR FROM DIAL STRIP TERM. 2 TO TERM. 1. AT STATIONS WITH RINGING ON A WIRE REVERSE A&B LEGS OF EXCH. LINE
3. BIAS SPRING FITTED TO HOLD THE BELL ARMATURE TO THE RIGHT HAND POLE PIECE LOOKING AT THE BELLS WITH THE GONGS UPPERMOST.
4. ALL WIRING NOT OTHERWISE SPECIFIED TO BE 23S.W.G.
5. ALL TERMINALS ARE ON INSTRUMENT STRIP CONN UNLESS OTHERWISE SPECIFIED.
6. ARROWS INDICATE DIRECTION OF WINDING.

"OBSOLETE"

		<input type="checkbox"/> SLOW RELEASE		<input checked="" type="checkbox"/> SLOW OPERATE	
AUTOMATIC TELEPHONE TABLE COMBINED SET (ONE PIECE) BPO 332 TYPE MODIFIED FOR 2 PARTY LINE WORKING WITH OR WITHOUT METERING					
OBSOLETE REF. ADDED (54997)		3A	3.12.62	DBK	
TITLE AMENDED (34545)		2A	26.5.55	MR	
CAPACITOR DESIGNATIONS & DIAL CORD CONNECTIONS REVISED (14420)		2	5.5.52	CUN	
AMENDMENT PARTICULARS			ISSUE	DATE	APP.
SWC 3		N.Z.P.O.			
DRAWN		CHECKED	WIRING	CIRCUIT	
3/10/52		3/10/52	3/10/52	3/10/52	
REF. - NZPO 21302A			SIZE	S	H
			GBW 12200		