



- NOTES**
1. FUSING: 0.5A PER CIRCUIT (U12)  
0.5A PER CIRCUIT (U21 - HEATERS)
  2. Ø FOR WIRING SEE GBW 12380 OR EQUIVALENT
  3. CONDENSER VALUES:
 

FREQY	TR1(C1)	TR2(C1)
600	0.063	0.200
750	0.050	0.160
900	0.042	0.133
  4. STRAP TERMLS. A, B, 1, 2, 3 & 4 AS REQUIRED FOR FREQUENCY ADJUSTMENT
  5. SHELF JACK U POINTS 1 & 3, 2 & 4 MAKE CONTACT WHEN RELAY SET IS REMOVED
  6. TERML. (15) STRAPPED TO ONE OF TERMLS. (20)-(23) FOR COARSE OUTPUT ADJUSTMENT IN 3db STEPS.  
TERML. (12) STRAPPED TO ONE OF TERMLS. (1)-(5) FOR FINE OUTPUT ADJUSTMENT IN 1db STEPS
  7. ALL WIRING NOT OTHERWISE SPECIFIED TO BE 25 SWG

AMENDMENT PARTICULARS

NO.	DATE	DESCRIPTION
1	15/12/54	ISSUE DATE
2	26/12/54	REVISION
3	4/12/57	REVISION
4	5/8/74	REVISION

REVISIONS: 180 OHMS (5/8/74)  
SCREEN ETHS. QUALIFIED; NOTE 9 DELETED (3/9/57)

GBW 12350

FIXED FREQUENCY OSCILLATOR (WITH VARIABLE OUTPUT)

SIZE M 50V 5

VALVE HOLDER VIEWED FROM WIRING SIDE

VALVE V1 HOLDER TAG 1  
VALVE V2 HOLDER TAG 1

