



**NOTES**

1. FUSE - 1.5A PER CIRCUIT.
2. WIRING OF PLUGGED IN PORTION TO BE 25 SWG. ALL REMAINING WIRING - 18/23 SWG UNLESS OTHERWISE SPECIFIED.
3. U9 & U11 TO BE STRAPPED WHEN CIRCUIT IS ASSOCIATED WITH AN UNDER 3db UNREPEATERED LINE.
4. IN ADDITION TO SHELF JACK POINTS U5 & U11, U14 & U16 TO MAKE CONTACT WHEN RELAY SET IS REMOVED.
5. Ø FOR WIRING SEE GBW 10640 OR EQUIV.
6. RELAY DR IS DIFFERENTIALLY CONNECTED.
7. RELAY G IS NORMALLY OPERATED.
8. WHEN THIS CIRCUIT IS USED ON METALLIC LINES OR AS PHANTOM CIRCUIT ON PHANTOMED LINES, DISCONNECT STRAP U2C-U30 SHOWN AND CONNECT STRAPS U10-U24, U25-U31 & U2C-U30 SHOWN. WHEN THIS CIRCUIT IS USED ON PHANTOMED LINES AS SIDE CIRCUIT, DISCONNECT STRAPS SHOWN AND CONNECT STRAP.

**PAHIATUA CAX ONLY**  
**NOT TO BE USED FOR NEW WORK**

EXPLANATORY ONLY

RESTRICTION ON USE APPROX. NOTE RENOVATED (2996) B. 8.5.64 0841 (27995)	A. 5.5.60	CE 393/3/67
AMPLIFICATION PARTICULARS	ISSUE DATE	APPR.
GBW 13030 MOD B	SIZE M	SOV. 1 W

**BOTHWAY TRUNK**  
**GENERATOR SIGNALING**  
**AND D.C. DIALING**  
**PAD CONTROL 2000 TYPE**