



- NOTES:-**
- FUSING:-SELECTOR & RELAYS 1.0A PER CCT. CHOKE 1.5A PER CCT.
 - RELAYS XY & Z TO BE ADJUSTED TO PROVIDE "FOR STEPPING SWITCH EVERY 300 M.S.
 - UNLESS OTHERWISE INDICATED ALL TERMINALS ARE ON STRIP CONNECTION AT REAR AND ARE DESIGNATED SCA (UPPER STRIP) & SCB (LOWER STRIP) IN WIRING RINS.
 - ALL WIRING TO BE 20 SWG UNLESS OTHERWISE SPECIFIED.
 - WHEN USED WITH "M" FINAL SELECTOR CCT. GBW 14400 USE CCTS. B1/6 ONLY.
 - Ø FOR WIRING SEE GBW 13730 OR EQUIV.
 - ADJUST VOLTAGE ON SITE TO GIVE SATISFACTORY RINGING.

CODE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
A	[Timing diagram with pulses]																																																	
D	[Timing diagram with pulses]																																																	
M	[Timing diagram with pulses]																																																	
S	[Timing diagram with pulses]																																																	
START	[Timing diagram with pulses]																																																	
HOLD	[Timing diagram with pulses]																																																	
TIME/MS	[Scale 0 to 300]																																																	

- N.Z. NOTES:-**
- A WHERE EXCESSIVE OVERHEATING OF CS UNISELECTOR COIL IS EXPERIENCED:-
 - (1) REMOVE WIRING SHOWN — AND
 - (2) ADD RESISTOR R12, AND WIRING SHOWN — 2-2.
 - B WHERE N.Z. NOTE APPLIES, REMOVE WIRE CSTJ1-PL3.

RETRACED	(86542)	6B	1-10-78	G.G.
N.Z. NOTE B ADDED	(30070)	6B	9-6-78	B.S.H.
N.Z. NOTE A ADDED	(20124)	6A	15-12-71	B.S.H.
C14 CAPACITOR DELETED	(47657)	6	5-11-65	d.
AMENDMENT PARTICULARS	ISS. DATE		APPN	

UAX NZ13 RINGING CODES FOR 5 PARTY LINES

50V C

GBW 13760