



NOTES:-

1. CAPACITOR C7 FITTED DURING TEST TO TUNE OSCILLATOR TO 2000 CYCLES ±10%
2. ALL WIRING TO BE IN 0.7mm UNLESS OTHERWISE SPECIFIED
3. KPA & KPB KEY IN NORMAL POSITION CONNECTS 800 P.P.S.

NOTE 3

2000 PPS (KPA)	300 PPS (KPB)	TELE ON LINE (KTL)
4	4	2



RETRACED & METRICATED	(157771)	5A	16.5.78	RED
DESIGNATIONS C3 & C4 WERE REVERSED	(14353)	5	31.1.58	ACG
LKC 10 & 12 WERE NOT WIRED. LKB (-) & (+) REVD.	(68043)	4	30.10.56	CWH
DESTINATION OF A-B LINE & TELE LEADS REVISED.	(65732)	3	23.9.55	CWH
LKABC & LI-2 TAGS REDESIGNATED. DELETED C7, 9.		2	7.7.55	CWH
	(65152)	1		

AMENDMENT PARTICULARS	ISSUE	DATE	APPD
NZPO	DRAWN JD	CHECKED	WIRING
			CIRCUIT DEP

OSCILLATOR FOR TRANSMISSION TESTS

REF: _____ SIZE: S 50V -

14320

GBW