



- NOTES:-
1. FUSING:-1.5A PER 10 CCTS.(2 PLATES)
 2. Ø FOR WIRING SEE DIAG.705022 OR EQUIV.
 3. ALL WIRE UNLESS OTHERWISE SPECIFIED TO BE 6mm, PLATE WIRING TO BE 5mm.
 4. FOR "UNALLOTTED" CEASED OR T.O.S."LINES JUMPER,"NU"TAGS TO APPROPRIATE FINAL SELR.OUTLETS -+PF.& OMIT JUMPERS TO LINE CIRCUIT.
 5. JUMPERING IS PROVIDED BETWEEN THE "LINE CIRCUITS" STRIP CONN., & "LINE GROUPING" STRIP CONN. TO ALLOW 5 OR 10 PARTY LINE WORKING. FOR 5 PARTY LINE WORKING JUMPER EACH FINAL SELR.OUTLET TO A LINE CIRCUIT. FOR 10 PARTY LINE WORKING JUMPER TWO FINAL SELR.OUTLETS TO A LINE CIRCUIT.

SUPERSEDED BY GBW.13640 FOR NEW WORK

SLOW RELEASE SLOW OPERATE

RETRACED WIRE SIZES METRICATED (157772) (66258)				1A	1B-5-78	R.E.D.
AMENDMENT PARTICULARS				ISSUE	DATE	APPD
N.Z.P.O.				G.E.C. 705010 SIZE: S 50V		
GBW				14470		

SUBSCRIBERS LINE CIRCUIT
 FOR MULTI-PARTY LINE DUTY
 UAX. N.Z. 13R.