



MANUAL BOARD OR
DIRECTORY SERVICE DESK
EXPLANATORY ONLY

FROM
SELECTOR
LEVELS

TRAFFIC
RECORDER
(WHEN REQ'D)

NOTES:-

1. FUSE F-15A PER CIRCUIT.
2. ALL WIRING TO BE 25 SWG. UNLESS OTHERWISE SPECIFIED.
3. Ø FOR WIRING SEE GBW.10640 OR EQUIV.
4. SHELF JACK POINTS U9 & U11 TO MAKE CONTACT WHEN RELAY SET IS REMOVED.
5. P WIRE IS JUMPED TO BUSYING OCT. GBW. 15330. WHEN REQUIRED.

BATT. FUSE BK 225WG U12

ETHETH BAR R 225WG. U11

BATT. W.-U12-RB1b-Bc-R1b-R3b

ETHR.-U11-L521-5d-1Ab-1Ad-OHd
RB1d-5522-55a-B5-TJ1

FU DANNEVIRKE

RING TONE SUPPLIED VIA 0.05 UF CAPACITOR FROM RINGING SUPPLY. (85185)		MOD. A 24-9-68
AMENDMENT PARTICULARS	ISSUE DATE	APPROV. REF.
NZPO	DESIGNED	CHECKED
	WIRING	CIRCUIT

SELECTOR LEVEL RELAY SET
WITH RESISTOR BALANCE
MAIN & SAT. LEVELS IN S.C.E.
MAIN EXCHANGE
2000 TYPE

GBW 14980 MOD. A.