



- NOTES:-
1. FUSE - 1.5A PER CIRCUIT.
 2. ALL WIRING TO BE 25 SW/G UNLESS OTHERWISE SPECIFIED.
 3. Ø FOR WIRING SEE ASSOCIATED COMMON SERVICES DIAGRAM. GBW 15890 OR EQUIV.
 4. RELAY DR IS DIFFERENTIALLY CONNECTED.

BATT. V: U12-R1b-R2b-R3b-Ae-SSe-LAe-DS 14-
PSb-PSe-LSe-DRe

ETH. R: U11-A22-A3-S1-SS70-SS8-DS 5 TO
DS 25-LS1-B1-B5-CA1-DRI-DRA4

ETH BAR R 22 SW.G U11
3A2

BATT FUSE V 22 SW.G U12
3B2

INCOMING JUNCTION CIRCUIT TO MANUAL BOARD (CODE 11) S.C.S. 2000TYPE.			
URI - PAD WAS 2.5db. (39730)	2	18.10.71	B.S.H
AMENDMENT PARTICULARS	ISSUE	DATE	APPR REF. S245440
N.Z.P.O. SIZE: S	DRAWN EE	CHECKED N.C. 9/18	WIRING N.C.
CIRCUIT			GBW 15760