COIN COLLECTORS — POSTPAY — 193GL, HL COMMUNITY DIAL OFFICE SERVICE LOCAL BATTERY — CONNECTIONS

1.00 INTRODUCTION

This section covers the combination of apparatus, circuit diagram, and connections for the 193GL and HL coin collectors when used for postpay service on a 10-cent initial charge basis as a local battery talking—common battery signaling station in community dial office service areas.

2.00 GENERAL

2.01 The line limits within which the coin features of this coin collector will operate, when used as a local battery talking—common battery signaling station, is dependent upon the type and arrangement of the central office equipment to which it is connected. This coin collector shall not be used at such stations without proper authorization.

2.02 The 193GL and HL coin collectors are used with the 634YD subscriber set when its use does not conflict with the requirements in 2.01.



FIG. 1—193GL, HL DIAL SET—EQUIPPED WITH APPARATUS BLANK

TABLE A—COMBINATION OF APPARATUS—LOWER HOUSING AND BACKPLATE

| Type Collector | Components | | | | | | |
|-------------------|------------|-----------------|--------------------|-----------------|-------------|----------|--|
| | Handset | Handset Cord | Induction Coil* | Capacitor* | Resistor | Varistor | |
| 193GL, HL | F1B | H3AE or H3S | 101B | 452C or 195C | 31A and 37A | 63CH | |

^{*}Standard equipment, not wired in circuit, when used as a local battery station.

TABLE B-COMBINATION OF APPARATUS-UPPER HOUSING

| Type Collector | Components | | | | | | |
|-------------------|------------|-----------------|-----------------|--------------|--------|------------------------|--|
| | Dial | Dial Adapter | Capacitor | Resistor | Filter | Coin Chute Assembly | |
| 193GL | 5HH 6C | 56A 63A | 452A or 452B | KS-13490, L2 | 61R | P-340224 | |
| 193HL | | | | | | P-340225 | |

Note: Assembly P-340224 consists of P-340042 chute, P-349747 electromagnet (polarized), and gong signal assembly. Assembly P-340225 differs in that it is equipped with a P-340043 chute.

3.00 CONNECTIONS

3.01 The circuit diagram in this section is shown on a foldout page so that it may be associated with the circuit diagram of the appropriate subscriber set to provide complete information for the connection of station apparatus.

3.02 The designations on the transfer contact terminals in some upper housings are different than shown herein. Corresponding terminals are as shown in Table C.

TABLE C-UPPER HOUSING

| Upper Housing | Terminals | | | | | | |
|---------------|-----------|---|-------|-------|-------|--|--|
| Original | w | Y | BK-YY | BB-YY | 5* | | |
| Replacement | w | Y | YY | BB | BK-YY | | |

^{*}Terminal 5 is not always furnished.




Fig. 2—Lower Housing and Backplate




FIG. 3—UPPER HOUSING

3.03 Circuit diagram of 193GL, and HL coin collector when used with 634YD subscriber set.

