

STATION SYSTEMS
50A CONFERENCE SET
CIRCUIT

CHANGES

B. Changes in Apparatus (Components)

B.1 In FS1

<u>Removed</u>	<u>Replaced By</u>
C4 Capacitor 603A, 4 μ F (Z option)	C4 Capacitor 601A, 5 μ F (Y option)

B.2 In CPS2

<u>Removed</u>	<u>Replaced By</u>
R24 Resistor KS-16645 L1, 24 ohms	R24 Resistor 237A, 1 ohm

D. Description of Changes

D.1 Option Index added to Sheet Index

D.2 In FS1; LSPR for CP2 was changed to
PWRR27 for CP2 was changed to
R28

ICJ at CP4 was changed to J

D.3 In App Fig. 1:

CPS1 Dwg No. 84028365 was changed to
840284400.CPS2 Dwg No. 840283873 was changed to
840284426.Capacitor C4, 603A (Z option) was
changed to 601A (Y option).D.4 In Circuit Notes, Z and Y options
were added to Note 103.D.5 In CPS1 (sheet J1B) circuit pack
code and assembly drawing No. was
changed to 840284400.D.6 In CPS2 (sheet J2A), the value of
resistor R24 was changed to 1.0 ohm.D.7 In CPS2 (sheet J2B) circuit pack
code and assembly drawing No. was
changed to 840284426 and resistor R24
was changed from KS-16645 L1, 24 ohms to
237A, 1.0 ohm.

BELL TELEPHONE LABORATORIES, INCORPORATED

DEPT 3325-WDG-FEF