

V-1050C - 5 WATT BI-DIRECTIONAL HORN/ ONE-WAY AMPLIFIER ASSEMBLY

INTRODUCTION

The V-1050C is a Bi-directional, 5 Watt One-way Amplified Horn Assembly. The V-1050C consists of two horn speakers positioned on a common mounting frame with a built-in one-way 5 Watt amplifier.

SPECIFICATIONS

Features

- 5 Watts
- Self-contained amplifier and volume control
- Simplifies paging horn installation
- Vertical or horizontal mounting

Dimensions/Weight

- 9.60" H x 8.20" W x 9.30" D
(24.38cm H x 20.83cm W x 23.62cm D)
- Weight: 6.3 lbs. (2.86 Kg)

Power Requirements

- Unfiltered -24VDC ("B" Battery) 300mA maximum

Environment

- Temperature: -20 to +55 degrees C
- Humidity: 0 to 95% non-precipitating

DESIGN

General

The V-1050C may be used to provide one-way paging from any Valcom one-way or talkback page control unit. A standard Valcom paging system is made up of three basic components:

- Page Control Unit
- Speakers
- Power Supply



Consult Valcom's One-way Paging VSP for detailed information on selecting the control unit and power supply.

Special Applications

The V-1050C may be connected directly to the speaker in most electronic key telephones to amplify the level of the speaker and broadcast it to a large area. A power supply will also be required.

The V-1050C may be used to expand a constant voltage (25/70/100 Volt) paging system without placing an additional load on the amplifier by adding a V-1095, 70V Paging Expander. A power supply will also be required.

Coverage

Refer to Table 1 for coverage of this horn assembly. The first figure given is the side to side distance to use when mounting the horns. The second figure is the front to back distance between horns. The third figure is the total square footage the assembly will cover.

Table 1

Location	Side/ Side	Front/ Back	Square Feet
Quiet	70'	140'	9,800
Moderate	50'	100'	5,000
Noisy	30'	60'	1,800
Very Noisy	20'	40'	800

INSTALLATION

Connections

Four conductor wire is required for the V-1050C. Standard 22 or 24 gauge station or JKT is acceptable. Shielded wire is not required or recommended. Connections are as follows:

Green	Tip
Red	Ring
Black	Ground
White	-24VDC

Tip and Ring are from the page control unit; -24VDC and ground are from the power supply.

The specifications in Tables 2 and 3 must be met when wiring this speaker assembly.

Table 2

Maximum Number of Horns per Audio Run	
Wire Run in Feet (22 AWG)	# of Horns
200	150
400	100
800	50
1600	25

Table 3

Maximum Number of Horns per Power Run	
Wire Run in Feet (22 AWG)	# of Horns
200	4
400	2
800	1
1600	0

Mounting

The V-1050C should be mounted 12' to 25' high to obtain optimum results and may be used for either interior or exterior applications.

- Loosen the wing nut to remove both speakers from the mounting bracket. Position the mounting bracket as desired and then re-attach speakers to the bracket.

Both horns of the V-1050C may be rotated or moved up and down to obtain the desired position by loosening the position adjustment knob at the bottom of each horn approximately one turn, locating the desired angle placement and re-tighten the knob.

Connection to an electrical box is accomplished by channeling the wire through the hole in the base. Holes are punched in the plate for mounting to a double-gang square box, single-gang or octagon box.

TECHNICAL ASSISTANCE

When trouble is reported, verify there are no broken connections between the telephone and the ringer. Ascertain volume control is turned up.

Assistance in troubleshooting is available from the factory. When calling, you should have a VOM and a test set available and be calling from the job site. Call (540) 563-2000 and ask for Technical Support, or call (540) 767-1555 for Valcom 24-hour Faxback System or visit our Website at <http://www.valcom.com>.

Valcom equipment is not field repairable. Valcom, Inc. maintains service facilities in Roanoke, VA. Should repairs be necessary, attach a tag to the unit clearly stating company name, address, phone number, contact person and the nature of the problem. Send the unit to:

Valcom, Inc.
Repair and Return Dept
5614 Hollins Road
Roanoke, VA 24019-5056

Troubleshooting Chart	
Symptom	Solution
No Output	A. Verify -24VDC on the white lead with ground (+) on the black. B. Verify audio is present on the green and red leads (Monitor with a lineman's test set at the speaker). C. Verify volume control turned up (Clockwise).

VALCOM LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim;
2. the defect is not the result of damage, misuse, or negligence after the original shipment;
3. the product has not been altered in any way or repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged);
4. freight charges for the return of products to Valcom are prepaid;
5. all units 'out of warranty' are subject to a service charge. The service charge will cover minor repairs (Major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties, expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.

Headquarters: Valcom, Inc. 5614 Hollins Road Roanoke, VA 24019-5056 Phone: (540) 563-2000 FAX: (540) 362-9800	In Canada CMX Corporation 35 Van Kirk Drive #11 and 12 Brampton, Ontario L7A1A5 Phone: (905) 456-1072 FAX: (905) 456-2269
--	--